




HUG HYDRONICS™



HUG Hydronics Electric Tankless Water Heaters

High Quality Tankless on-demand hot water heaters for the patent pending HUG Hydronic in-floor heat distribution system.



Electric On Demand Tankless Water Heater Key Features

- Compact Size & Ease of installation
 - Easily mounts to the wall
- Easy Maintenance
 - No screens to service - No moving parts
- Scale Reduction Technology
 - Power sharing technology reduces scale
- 5-Year Warranty
- See details at - www.statewaterheaters.com & <https://www.statewaterheaters.com/lit/spec/res-elec-tankless/sbess00119.pdf>



HUG HYDRONICS™



Electric On Demand Water Heater Installation Notes:

1. Mount the heater about 6 inches to 1 foot above the tank, ideally - [refer to the user manual](#) *If the heater needs to be located further above, please contact HUG Hydronics Technical support.*
2. Install the required circuit breaker and connect the wiring - refer to the user manual
3. Connect the (2) brass fittings (HDW-0000029) provided with the heater
4. Connect the heater hoses from the tank using the clamps (HDW-0000031) provided



ELECTRIC HEATER SPECIFICATIONS

Part Number	Description	Voltage (V)	Current / Breaker (A)	Watts (KW)	Dimensions (HxWxD)	Ship Weight
1020-12-AF	12.2KW Electric Tankless Water Heater, 2 chamber (C2VS-120E) with 3/4" fittings	240	64 / 1x70	12.2	17-3/4" x 11-1/2" x 6-1/8"	13 lbs
1020-18-AF	18KW Electric Tankless Water Heater, 4-chamber (R4LS-180E) with 3/4" fittings	240	94 / 2x50	18	17-3/4" x 11-1/2" x 6-1/8"	20 lbs



HUG HYDRONICS™

